

R-2017

FIRE EXTINGUISHER BRACKET FOR ('69-'73 911) INSTALLATION INSTRUCTIONS

This fire extinguisher bracket is designed to mount a 2.5 lb fire extinguisher in front of the driver or passenger side seat.

Install this bracket on the *driver or passenger side.

*Note: this mount is stationary and limits the full range of seat motion available.

Our mounting bracket adapts the bracket supplied with the extinguisher to the seat. The hole pattern on our bracket matches the hole pattern on the bracket supplied with *AMEREX* extinguishers. If your bracket does not match our hole pattern drill (4) 1/4" diameter holes in your bracket using the supplied template.

Step 1

Move seat to rear most position. Remove both front seat track mounting bolts on each side.

Step 2

Raise the front of the seat enough to slide the mounting bracket between the seat tracks and the floor.

Step 3

Reinstall the front seat track mounting bolts. (always check hardware for full thread engagement, replace bolts if necessary.)

Step 4

Attach the mounting bracket supplied with the fire extinguisher to the Brey~Krause mount using the supplied hardware.

Performance driving events are by nature potentially hazardous to your health. Brey~Krause Mfg. Co. Inc. shall not be liable for injury, consequential, or other types of damages resulting from the use or misuse of our products. Proper installation of these parts is critical and should only be done by a professional shop.

